


Picture		
Model	Argus Series B740X	
Categories	Parameters	Contents
Video & Audio	Image Sensor	1/1.8" CMOS sensor
	Resolution	5120x1440 (8 megapixels) @15fps
	Lens	f=4mm, fixed
	Video Compression	H.264/H.265
	Field of View	Horizontal: 180° Vertical: 50°
	Infrared Night Vision	NO
	Color Night Vision	With spotlights: 3pcs/2W/6500K
	Frame Rate	Main stream: 10fps - 15fps (default: 15fps) Sub stream: 10fps - 15fps (default: 15fps)
	Code Rate	Main stream: 1024Kbps - 4096Kbps (default: 2048Kbps) Sub stream: 256Kbps - 1024Kbps (default: 512Kbps)
Audio	Two-way audio	
Power Requirements	Battery	5000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel 2 (6W)
Bluetooth	Bluetooth Standard	Bluetooth V5.0
Interface	Power Port	USB Type-C port
	SD Card Slot	Supports Max. 128GB microSD card
	Reset Button	YES
	Audio In/Out	Built-in microphone and speaker
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n/ac/ax
	Operating Frequency	2.4GHz/5GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	Smart Alarm	PIR detection; motion detection; person detection; vehicle detection; animal detection
	PIR Detecting Distance	Adjustable, up to 10m (33ft)
	PIR Detecting Angle	170° horizontal
	Recording Modes	Triggered recording
	Time Lapse	YES
	Smart Home Compatibility	Google Assistant
	Home Hub Compatibility	YES
Cloud Storage	Supports Reolink Cloud (available in selected countries)	
Working Environment	Operating Temperature	-10°C~55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
	Weatherproof	IP66
Mechanical	Dimensions	128*87*80mm
	Weight (Without Bracket)	400g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.