Picture	realink	
Model	Hub1	
Device Management	Camera	Up to 8 Cameras
	Device Compatibility	All Reolink WiFi/PoE Cameras (Battery cams needs to be upgraded through the firmware support Hub)
	Safety Protection	Devices are not accessible individually ; must be accessed through Hub
Input/Output	HDMI	NO
	USB	NO
	Button	YES
	Power	DC 12V/1A
	Speaker	√ (MAX 115dB)
	Ethernet	1*10M/100M bit RJ45 Port for WAN
Storage	SATA	NO
	MicroSD Card Slot	Up to 512GB*2
	Backup Media	NO
	Storage Encryption	Protect privacy and anti-theft with advanced encryption features
Preview&Playback	Preview	APP, PC Client
	Playback	Smart Playback / Quick Events History
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n/ac/ax (WiFi 6)
	Operating Frequency	2.4/5 GHz
	Wireless Security	WPA/WPA2/WPA3
Sub 1G	Operating Frequency	868/915MHz
System	Network Protocols	TCP/IP, UDP, DHCP, P2P, UPNP, RTSP,RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	11 users (1 admin account & 10 shared accounts)
	Smart Home	Google Home
Working Environment	Operating Temperature	-10°C~+45°C
	Operating Humidity	10%~90%
Mechanical	Dimensions(mm)	95*95*161.8mm
	Weight	441g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.