

Features	Boss IR-2	Boss IR-200
Audio Quality	32 bit / 96 kHz AD/DA	32 bit / 96 kHz AD/DA
Processor	32bit floating point	32bit floating point
Amp Channels	2	1
Amp models	11 Guitar	8 Guitar + 3 Bass
Cabinets	11 linked per amp type	106 Guitar + 48 Bass
User IR	11	128
IR files compatibility	24 bit/96kHz up to 500 ms (Mono)	24 bit/96kHz up to 500 ms (Stereo)
IR Level and EQ settings	No	Yes per IR
Additional IR's from 3rd party	Standard IR's from Celestion Digital	From Celestion Digital
Room simulation	Ambience (Room, Hall, Plate)	Ambience (Room, Studio, Hall)
Number of Memories	2	128
Input	¼ inch Jack (Mono)	¼ inch Jack (Mono)
Output	¼ inch Jack (Stereo)	¼ inch Jack (Stereo) or double Mono
Separate Cabs for outputs	No	Yes
Amp /Cab Bypass	Yes/Yes	Yes/Yes
FX Loop	Yes (Stereo Return)	Yes (Stereo Return)
Aux Input	No	Yes
Headphones	Yes	Yes with Surround effect (WAZA-Air)
Global EQ	No	Yes (per output or linked)
Display	No	LCD monochrome
USB	USB-C	Micro USB
USB Audio	Yes	Yes
Apps	IR-Loader/Editor	Boss Tone Studio + IR-Loader
External Controllers	FS-5U, FS-6, FS-7	FS-6, FS-7, EV-30
MIDI	No	Full MIDI controllable via TRS MIDI jack
Bypass	Buffered	Buffered
Power	9volt battery or optional PSA power Adaptor	PSA Power adaptor included